

**ATTENTION: All Total Door Distributors & Sales Representatives**

**DATE: Oct 1, 2017**

**REGARDING: Total Door Power Supplies**

---

Total Door is always moving forward with product and process improvements. To that end, we will be upgrading to a new power supply, PS210. The upgraded power supply will be provided as complete assembly including an integrated enclosure.

Previous power supplies, PS100A and PS100ASA, will be available on a limited basis for currently active quotations and for future service orders.

### **PS210 SPECIFICATIONS**

**Input Voltage:**

- 120 VAC, 60 Hz,
- Input Fuse: 2 Amp Fuse @ 250VAC

**Output Voltage:**

- 2A @ 24VDC
- 1 Solid State I/O's - 2A auto resetting fused outputs
- Over-voltage protection
- Output Voltage trim pot

**Fire Alarm:**

- Fire alarm tie-in

**Electrical:**

- Temperature range: 0° to 49° C; 32° to 120° F
- Maximum humidity: 85%

**LED's:**

- Red = A/C Power indicator
- Green = D/C Output indicator

**Features & Benefits:**

- Linear design insures ample inrush/hold current for latch retraction
- Door mounted LED Power Indicator
- Easy to remove euro connectors

**Mechanical Details:**

- Enclosure dimensions: (11" W x 11" H x 4" D)
- 1/2" & 3/4" knockouts on all sides
- Hinge-less removable cover; Cam lock not provided
- Product Weight: 10lbs
- Shipment Weight: 11lbs

**Listed:**

- UL 294, 6<sup>th</sup> Ed.