

# **Pre-finished, 3-Ply Veneer by Others**

### 3-ply wood veneer is used for complex finishes or horizontal grain. Total Door is only able to provide single step stain finishes in-house.

### **Specifications:**

Thickness:	Min .100 to Max .115 inch
Veneer Face:	1/36" to 1/50" (1/42" nominal)
Cross Band:	HDF or Natural Aspen .060" thick
Backer:	1/36" to 1/50" (1/42" nominal) No open knots and no splits
Size:	2" wider & 2" longer than the door size NOTE: If doors have standard panics (P14), sheets must be 8" longer than door height

#### \*If veneer is not 3-ply and/or does not meet the above requirements, the material cannot be used\*

#### Procedures for wood veneer supplied by others:

- Mark with door numbers, if applicable
- Mark all sheets "Top" and "Bottom"
- Mark all sheets "Push" and "Pull" side of door, if applicable
- Include details if special alignment of veneer on door face is required
- No tape or adhesive material is to be applied to the face of the veneer

## Ship flat on a pallet with complete plywood coverage to prevent freight damage. If material is shipped in any other manner, shipment will be refused.

All shipments must contain the "Customer Supplied Veneer" packing slip.



# **CUSTOMER SUPPLIED VENEER PACKING SLIP**

PROJECT NAME:		
PROJECT/QUOTE NUMBER:		
VENEER SUPPLIER:	COMPANY:	
	THORE.	
SPECIES & CUT:		
Number of pieces		
Width & Length		
Thickness		
DISTRIBUTOR:	COMPANY:	
	PHONE:	
	CONTACT:	

DATE SHIPPED:

CHECK IF APPLICATION DRAWINGS ATTACHED

\*THIS COMPLETED FORM IS TO BE INCLUDED WITH EVERY SHIPMENT. WE SUGGEST SENDING THIS TO THE VENEER SUPPLIER TO INCLUDE WITH SHIPMENT\*

\*A COPY SHOULD ALSO BE SENT TO THE FACTORY PRIOR TO MATERIAL BEING SHIPPED FOR ADVANCED SHIPPING NOTICE\*